CROSS-CONNECTION DRINKING WATER PROGRAM

AN ORDINANCE PROVIDING WATER QUALITY FROM POLLUTION OR CONTAMINATION OF ANY KIND BY ADOPTING A CROSS-CONNECTION PROGRAM. THIS PROGRAM WOULD MEET THE REQUIREMENTS AND PROCEDURES SET BY THIS ORDINANCE AND THE OREGON STATE HEALTH DIVISION, ADMINISTRATIVE RULE NO. 333-61-070.

SECTION 1. Definitions. "Cross-connections" are any source or substance of water entering the city's water system other than provided through the regulated city water system.

"User" means the resident receiving water from the city system.

"Water supplier" means the city public works department.

SECTION 2. Public Works Regulations. As determined by the water supplier upon inspection and evaluation of premises at any time, all new and existing water users with cross connection, shall install an appropriate back-flow prevention device. Water supplier shall test all back-flow devices immediately after installation and annually thereafter. Devices shall also be inspected upon relocation. Written reports shall be completed by the water supplier for all evaluations and inspections. Copies to be received by users.

SECTION 3. Fees. A fee of fifteen dollars will be charged to users for each inspection of back-flow devices.

SECTION 4. User's Requirements.

- A. Existing users shall be allowed six months to complete installation of back-flow devices. New users shall be required to complete installation of back-flow devices before turn-on of city water. Users stating "non-use" of cross-connection and with a disconnected pump, shall sign a statement of such including a clause to notify the city when used in the future;
- B. All back-flow prevention devices required by this section shall be of a type and model approved by the water supplier as required by the State Health Division for use in Oregon;
- C. Failure of users to comply with the requirements of this section shall allow the water supplier to discontinue water service to the user's premises until an appropriate back-flow prevention device is property installed or until and cause of the hazard is eliminated.

SECTION 5. Enactment; Emergency Declared. Whereas this Ordinance is required by the Oregon Department of Human Resources Drinking; Water Program, therefore, an Emergency is hereby declared to exist and this Ordinance shall be in full force and effect on and after the date of approval by the City Council and the Maydr.

APPROVED BY THE CITY COUNCIL ON THE 11 DAY OF HECEMber , 1995

MAYOR RON FORD

CT TY MANAGER JACQUELINE OAKLEY

CROSS-CONNECTION CONTROL PROGRAM

for THE CITY OF MONUMENT

The City of Monument, in the interest of preserving its water quality from pollution or contamination of any kind, adopts the following Cross-Connection Program. This program meets the requirements and procedures set by City Ordinance No. 95-1 and the Oregon State Health Division, Administrative Rule No. 333-61-070.

When a contamination of the city's water system exists, an inspection and evaluation of the premises shall be performed by a city personnel. In the event of an actual cross-connection, the user will install an approved back-flow device, or eliminate the cross-connection hazard. The device or control used shall be in accordance with any manuals of standard practice, pertaining to cross-connection control, approved by the Oregon Health Division, the City of Monument, and any requirements set forth the National Safe Drinking Act, FL 34-523, and all subsequent legislation.

The City of Monument Public Works Department shall regulate the location, installation and testing of any back flow device installed on its water system. Devices shall also be inspected and tested upon any relocation, corrective measure, disconnection or changes on private property, and shall be at the sole expense of the user of the water service. The cost of any changes in the city's system outside the property, or between the meter and the cut-off or disconnection, shall be the responsibility of the water supplier.

Inspection and evaluation of existing back-flow devices, or actual cross-connections shall be preformed for a fee of \$15.00 per inspection, a maximum fee of \$35.00 will be charged for each test of any existing or newly installed back-flow device. The cost of inspection and testing will be the sole responsibility of the user. The user shall pay at the time of billing. The frequency of testing shall be determined by the severity of the cross-connection hazard and the results of existing tests. Devices failing initial tests must be repaired and retested in three months. All devices with test ports shall be tested at least once per calendar year.