

00690

Goble Water Association Program Plan

Goble Water will keep a list of backflow devices and current test dates together with a copy of device testing records. This is in accordance with the following administrative rule, taken from the Oregon Health Division "Final Rule", dated 1/7/94.

333-61-070

(C) The water supplier shall maintain current records of backflow devices installed, inspections completed, and backflow device test results.

All backflow device assemblies for protecting the Community Water System shall be installed at the service connection to the premises where an approved airgap does not exist :

333-61-070

(4) Backflow prevention device assemblies for protecting Community water systems shall be installed at the service connection to premises where an approved airgap does not exist.

- (a) There is an auxiliary water supply which is, or can be connected to the potable water piping;**
- (b) There is piping for conveying liquids other than potable water, and where that piping is under pressure and is installed in proximity to potable water piping;**
- (c) There is intricate plumbing which makes it impractical to ascertain whether or not cross connections exist;**
- (d) There is backsiphonage potential.**
- (e) Cross connections or potential cross connections exist.**

Any property with an auxiliary water supply will have an approved reduced pressure backflow device installed at the point of service (water meter location) in accordance with the Health Department standards.

List of facilities :

dad\ccmcn

RECEIVED
APR 03 2007
Data Mgmt & Compliance
Drinking Water Program

Goble Water Association Cross Connection policy

In accordance with Oregon State Health Division administration rule 333-61-070, Goble Water Association will abide by the required Cross Connection policy taken from "Final Rule" 1/7/94. The following outline are excerpts taken from these administrative rules which would apply specifically to the Goble Water system.

(1) Water suppliers shall undertake programs for controlling and eliminating cross connections:

(a) In Community water systems, water suppliers shall carry out a local cross connection program consisting of the following elements:

(A) Local ordinance or enabling authority which authorizes discontinuing water service to premises for failure to install an approved backflow device or conduct a required annual test on a backflow device.

In accordance with the above requirement, Goble Water Association will authorize the discontinuance of water service to premises that do not have an approved backflow device installed, Water service may also be discontinued if there is no record of the required annual test on a backflow device in Goble's file.

Length of time from date of notice to discontinue water service to the actual termination of service is 30 days from date of notice.

333-61-070

(B) A written program plan which includes the following:

(i) A master list of facilities and premises which are subject to inspection, and the hazard level for each.

(ii) A current list of certified inspector staff and work responsibilities.

(D) The water supplier shall prepare and submit an annual written report to the Division using a format to be provided by the Division.

Goble Water Association's certified inspector as of October of 1996 is Mel Olson, Certification #2410. His work responsibilities include inspections and all follow-up communications.

Date adopted: 12/10/96 By: George R. Hyde
Goble Water Assoc